



Mowers - Side Discharge **4000** series

HM602/722/HP722

Ventrac **HM2** series Side Discharge Mowing Decks are designed and built to be the best cutting and longest lasting finish mowers available. A rugged all steel reinforced carrier frame incorporates a full length rear roller that maximizes grass striping of this ground floating deck.

The progressive flow deck design allows for grass to move quickly and efficiently out the discharge chute improving the quality of cut. Ventrac's LAS (Linear Adjustment System) provides cutting height selection of 1 $\frac{1}{8}$ to 4 $\frac{3}{4}$ inches (2.86 to 12 cm). A single hand adjustment lever allows for a quick change in cutting height.



Ventrac's **RTF** (Return To Form) Discharge Chute allows you to come in contact with obstacles and not damage the chute, it simply returns to its original form. No longer will you have to worry about bending or removing this important safety item.



The deck can quickly be tilted to a near vertical position for cleaning, transportation, storage or sharpening blades. Simply remove two pins, flip the deck up and reinstall the pins, it is just that simple.



The **Ventrac HP2 deck** is the same in design as the **HM2** decks except the mower is offset to the left side 6 $\frac{1}{2}$ inches. This aids in mowing along ditches, ponds and increased trimability around obstacles. The offset also makes for a smaller cutting radius to the left increasing productivity.

Standard Features:

- Flip-Up Deck
- Ventrac's RTF Discharge Chute
- Single-lever Linear Adjustment System
- Full-floating Deck
- Ventrac Mount System

Optional Accessory:

- Mulching Kit



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com

Specifications

Mowers - Side Discharge **4000** series HM602/722/HP722

	HM602	HM722	HP722
Stock Code	39.55105	39.55106	39.55107
Deck Type	Front-Mount	Front-Mount	Front-Mount
Deck Suspension	2 front tires (13 x 5.0 x 6 inches) (33 x 12.7 x 15.24 cm) with full width rear roller		
Width of Cut	Approx 60 inches (152 cm)	Approx 72 inches (183 cm)	Approx 72 inches (183 cm)
Number of blades/type	(3) 20 1/2 inch (52 cm) low lift	(3) 24 3/4 inch (63 cm) low lift	(3) 24 3/4 inch (63 cm) low lift
Cutting Height Range			
Low Position	1 1/8 - 4 1/8 inches (2.86-10.5 cm)	1 1/8 - 4 1/8 inches (2.86-10.5 cm)	1 1/8 - 4 1/8 inches (2.86-10.5 cm)
High Position	1 3/4 - 4 3/4 inches (4-12 cm)	1 3/4 - 4 3/4 inches (4-12 cm)	1 3/4 - 4 3/4 inches (4-12 cm)
Cutting Positions	13	13	13
Cutting Height Adjustment	Single Lever, Quick Select		
Deck Construction	Multi-Gauge, 5/16 inch (7.9 mm) at spindle mount		
Spindles/Pulleys	Field Serviceable w/ top grease fittings		
Anti Scalp Roller	Front Center	Front Center	Front Center
Discharge Deflector	Rubber	Rubber	Rubber
Optional Accessory			
Mulch Kit Part Number	39.55150	39.55151	39.55151
Dimensions			
Length	52 inches (132 cm)	58 inches (147 cm)	58 inches (147 cm)
Width	73 inches (185 cm)	85 inches (216 cm)	85 inches (216 cm)
Height	16 inches (40.6 cm)	16 inches (40.6 cm)	16 inches (40.6 cm)
Weight	385 lbs (175 kg)	450 lbs (204 kg)	450 lbs (204 kg)
Shipping Weight	495 lbs (225 kg)	560 lbs (254 kg)	560 lbs (254 kg)
Shipping Dimensions (LWH)	63.5x47.5x22.5 inches (161x121x57 cm)	75.5x52.25x22.5 inches (192x133x57 cm)	75.5x52.25x22.5 inches (192x133x57 cm)

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
 330.683.0075 • 1.866.VENTRAC
 Fax: 330.683.0000
 www.ventrac.com • info@ventrac.com