

The HQ680 **Tough Cut Mower** is designed for mowing high grass, thick weeds and brush. A large baffled front opening allows brush to enter for cutting and hinders debris from escaping.

Three heavy-duty blades counter rotate to cut and drop materials evenly without windrowing. Capable of cutting material up to an inch in diameter, the HQ680 makes short work out of heavy brush.

The Tough Cut can be adjusted to three cutting heights: 3, 3 $\frac{5}{8}$, and 4 $\frac{1}{4}$ inches. Easy servicing of belts and pulleys is provided by the hinged and removable cover. The tilt-up deck provides easy access to the blades.



Standard Features:

- Rear Adjustment for deck pitch
- Heavy Duty Blades
- Tilt up Deck
- Ventrac Mount System

Optional Accessory:

- Swivel Wheel Kit



Specifications

Tough Cut HQ680

4000
series

HQ680

Stock Code	39.55104
Deck Style	Totally enclosed- flexible front shield
Deck Suspension	Gauge Wheels, Tractor
Width of Cut	68 inches (172.7 cm)
Number of Blades/Type	3 blades, 5/16 x 2 -1/2 x 23 inches (79mm x 6.35cm x 58cm)
Cutting Heights	3, 3-5/8, 4-1/4 inches (7.6, 9.2, 10.8 cm)
Cutting Positions	3 (8 heights with Swivel Wheel Kit)
Deck Construction	Multi Gauge, 5/16 inch (7.9 mm) at spindle mount
Spindles/Pulleys	Field serviceable w/top grease fittings
Gauge Wheel adjustments	3 - 7 inches (7.6 - 20.3 cm)

Optional Accessory

Swivel Wheel Kit	70.8054
------------------	---------

Dimensions

Length	45 inches (114 cm)
Width	69 inches (175 cm)
Height	18 inches (46 cm)
Weight	360 lbs (163 kgs)
Shipping Weight	449 lbs (204 kgs)
Shipping Dimensions (LWH)	73x46.5x19 inches (185x118x48 cm)

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com