

The KP540 **Power Rake** is designed for leveling rough ground and new yard installations, as well as removing surface rocks and debris. Its compact design allows the operator to work in tight quarters including around corners and edges.

Seventy-two replaceable carbide tips pulverize and refine the soil. Materials can be moved forward or to either side by hydraulically angling the drum left or right. The drum can also be reversed to allow back-dragging of soils and cleaning off debris. A rotating handle raises or lowers the rotor in 1/8th inch increments allowing 3½ inches of travel.

Adjustable side wings can be lowered on both sides for routing material.



### Standard Features:

- Single Rotating Handle Height Adjuster – for fast and accurate adjustments
- Replaceable Carbide Tips (without removing the rotor)
- Forward & Reverse Rotation from the operator seat
- Hydraulic Driven Rotor
- Hydraulic Power Angle Control
- Adjustable End Plates for material routing
- Ventrac Mount System



# Specifications

# Power Rake KP540

4000  
series

## KP540

Stock Code	39.55435
Carbide Tips (Replaceable)	72
Power Angle	18 degrees
Bidirectional - on Rotor	Forward/Reverse
Dribble Gates	Adjustable
Filter	10 micron

## Dimensions

Length	59 inches (150 cm)
Width	63 inches (160 cm)
Height	36 inches (91.5 cm)
Rotor Width	54 inches (137 cm)
Height Adjustments (1/8th inch increments)	3 1/2 inches (8.9 cm)
Weight	536 pounds (243 kg)
Shipping Weight	677 pounds (307 kg)
Shipping Dimensions (LxWxH)	65x48x37 inches (165x122x94 cm)

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667  
330.683.0075 • 1.866.VENTRAC  
Fax: 330.683.0000  
[www.ventrac.com](http://www.ventrac.com) • [info@ventrac.com](mailto:info@ventrac.com)