



# V-Blade KV552

3000 series  
4000 series

The 55 inch side Ventrac KV552 V-Blade maximizes efficiency with the ability to quickly change from V plow to Scoop to straight blade, all from the convenience of Ventrac's exclusive S.D.L.A. control system. With a 48" V width, the KV552 is ideal for walks and areas that larger blades are unable to plow.

Standard features include hydraulically activated wing cylinders, mechanical trip, adjustable cast iron skid shoe discs, reversible high carbon hardened steel cutting edges, and a center shoe for gliding over rough terrain. Pivot points are fully greasable to ensure proper operation, even in the worst environments.

The KV552 V-Blade fits Ventrac 3000 and 4000 series tractors, and requires the 12V switch and plug kit.



## Standard Features:

- Hydraulically angle either wing
- Adjustable cast iron skid shoe discs
- Adjustable Spring controlled trip mechanism
- Trip Lockout Pin for Digging in material
- Reversible, Changeable Cutting Edge
- Center mounted skid shoe
- Ventrac Mount System  
(Requires 12 Volt Switch Plug Kit)

## Optional Accessories:

- Top Deflection Flap
- 6 and 12 inch Flare Extension kits
- Polyurethane Cutting Edge



Adjustable cast iron skid shoe discs



Pulled Back



Extended



Forward

Hydraulically angle either wing



328 East Water St • PO Box 148 • Orrville, OH 44667  
330.683.0075 • 1.866.VENTRAC (836.8722)  
Fax: 330.683.0000  
www.ventrac.com • info@ventrac.com

# Specifications

# V-Blade KV552



|   | <b>KV552</b>          |
|---|-----------------------|
| Stock Code  | 39.55271              |
| Required 12 Volt Switch/Plug Kit for 4000 Series    | 70.4039               |
| Required 12 volt Switch/Plug Kit for LE3100, LE3200 | 70.3016               |
| Hydraulic Power Angle                               | Independent cylinders |
| Blade Wing Selection                                | Electric Solenoid     |
| Spring Trip   | Mechanical On/Off     |
| Max Wing Angle (Left/Right)                         | 30 Degrees            |
| Adjustable Skid Shoes                               | Standard              |

## Optional Accessories

|   |         |
|---|---------|
| Top Deflection Flap                       | 70.8044 |
| Flare Kit, 6 inch extension (15 cm)       | 70.8045 |
| Flare Kit, 12/6 inch extension (31/15 cm) | 70.8046 |
| Straight Extension Kit, 6 inch (15 cm)    | 70.8047 |
| Polyurethane Cutting Edge                 | 70.8048 |

## Dimensions

|                                 |  |
|---------------------------------|--|
| Length, Wings Back              | 38 inches (96 cm)                        |
| Length with 3000 Series Tractor | 96.25 inches (244.5 cm)                  |
| Length with 4000 Series Tractor | 105.75 inches (269 cm)                   |
| Width, Wings Back               | 48 inches (122 cm)                       |
| Width, Wings Straight           | 55 inches (140 cm)                       |
| Width, Wings Forward            | 48.5 inches (123 cm)                     |
| Height                          | 24 inches (61 cm)                        |
| Weight                          | 240 lbs (109 kgs)                        |
| Shipping Weight                 | 372 lbs (169 kgs)                        |
| Shipping Dimensions (LWH)       | 52.25x35x27.125 inches<br>(133x89x69 cm) |

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667  
330.683.0075 • 1.866.VENTRAC  
Fax: 330.683.0000  
www.ventrac.com • info@ventrac.com