



Mowers - Side Discharge LM440/520/600

3000
series

Ventrac LM **Side Discharge Mowers** have cutting widths of 44, 52 and 60 inches (112, 132, 152 cm) and utilize a rugged all steel frame design, which suspends the Ventrac's discharge deck. This design gives you a high efficiency grass discharge for a better quality of cut by moving more grass efficiently through the deck tunnel. With the removal of two pins beneath the cross frame, the deck can be easily tilted to a near vertical position for maintenance and storage.

These mowers, equipped with a full width rear roller and wide pneumatic front swivel tires float over terrain independent of the tractor. The weight transfer system on the 3200 (optional on 3100) reduces mower weight on the ground and increases the traction and stability of the tractor.

LAS, a unique Linear Adjustment System, provides cutting height selections between 1 ½ and 3 ¾ inches (4 and 9.525 cm). A single handle with a slight outward pull allows for a quick and easy change in cutting height selection. A slide release allows the handle to be returned to deck level, preventing it from catching on low branches and shrubs.



All Ventrac LM finish mowers feature a full width rear roller for the ultimate in yard striping. These professional grade mowers are built to give you maximum performance and productivity.



Standard Features:

- Flip-Up Deck
- Single-lever Linear Adjustment System
- Field-Serviceable Spindles
- Full-floating Deck
- Ventrac Mount System

Optional Accessory:

- Mulching Kit



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com

Specifications

Mowers - Side Discharge LM440/520/600

3000
series

	LM440	LM520	LM600
Stock Code	39.35104	39.35100	39.35101
Deck Type	Front Mount, side discharge	Front Mount, side discharge	Front Mount, side discharge
Deck Suspension	2 front tires with full width rear roller		
Width of Cut	Approx 44 inches (152 cm)	Approx 52 inches (132 cm)	Approx 60 inches (152 cm)
Number of blades/type	(3) 15 inch (38 cm) low lift	(3) 18 inch (45 cm) low lift	(3) 20 1/2 inch (52 cm) low lift
Cutting Height Range	Approx. 1.5-3.75 inches (3.8-10 cm)	Approx. 1.5-3.75 inches (3.8-10 cm)	Approx. 1.5-3.75 inches (3.8-10 cm)
Cutting Positions	10	10	10
Deck Height Adjustment	Single Lever, Quick Select		
Deck Construction	Multi-Gauge, .22 inch (56 mm) at spindle mount		
Spindles/Pulleys	Field Serviceable w/ top grease fittings		
Anti Scalp Roller	Front Center	Front Center	Front Center
Discharge Deflector	Pivots up with spring tension downward		
Optional Accessory			
Mulch Kit	39.35152	39.35150	39.35151
Dimensions			
Length	41.75 inches (106 cm)	45 inches (114 cm)	45 inches (114 cm)
Width	54 inches (137 cm)	63 inches (160 cm)	70 inches (177 cm)
Deck Height	13 inches (33 cm)	13 inches (33 cm)	13 inches (33 cm)
Weight	220 lbs (286 kgs)	273 lbs (124 kgs)	310 lbs (141 kgs)
Shipping Weight	286 lbs (130 kgs)	339 lbs (154 kgs)	395 lbs (179 lbs)
Shipping Dimensions (LWH)	47.5x39x19 inches (121x99x48 cm)	56x41.5x19 inches (142x105x48 cm)	63.3x47x19 inches (161x119x48 cm)

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com