

The LQ450 **Field Mower** is designed to cut heavy grass and small brush growth. Two counter-rotating blades discharge the cut grass to the center rear. Suspended front chains allow tall grass to be cut more effectively and reduce the potential for front discharge. Three pins provide three cutting height options: 2¼, 3½, and 4¾ (5.7, 8.9, and 12.1 cm).

A single swivel tire is located on the front center frame of the mower. This position greatly reduces tree branch interference. Skid shoes on both sides provide anti-scalping and blade protection.

The tree shield kit can be installed for use on tree farms, vineyards, nursery's, etc. This shielding protects both the trees and the operator. Branch lifters and tractor tire covers are standard equipment with the tree shield kit.

**Note:** The Front Wheel Shields may have to be removed to mount some attachments.



### Standard Features:

- Hydraulic Lift
- 3 Cutting Heights
- Counter Rotating Blades
- Ventrac Mount System

### Optional Accessories:

- Tree Shield Kit
- Rear Weight Bracket
- Rear Suitcase Weights



# Specifications

# Field Mower LQ450

3000  
series

## LQ450

|                        |  |
|------------------------|--|
| Stock Code             | 39.35102                                       |
| Deck Type              | Front Mount, Rear Discharge                    |
| Deck Suspensions       | Single Center Tire                             |
| Width of cut           | 44.5 inches (approx) (113 cm)                  |
| Cutting Heights        | 2 1/4, 3 1/2, 4 3/4 inches (5.7, 8.9, 12.1 cm) |
| Deck Height Adjustment | 3 snap pins                                    |
| Deck construction      | 3/16 inch steel (4.8 mm),                      |
| Spindles/Pulleys       | Field Serviceable with top grease fittings     |

### Optional Accessories

|                                 |         |
|---------------------------------|---------|
| Tree Shield Kit                 | 70.3021 |
| Rear Weight Bracket             | 70.3017 |
| Suitcase Weights (Pk 2 Weights) | 70.0102 |

### Dimensions

|                           |                                   |
|---------------------------|-----------------------------------|
| Length                    | 55 inches (140 cm)                |
| Width                     | 46.5 inches (118 cm)              |
| Height                    | 18 inches (46 cm)                 |
| Weight                    | 243 lbs (110 kgs)                 |
| Shipping Weight           | 349 lbs (158 kg)                  |
| Shipping Dimensions (LWH) | 57.5x50x20 inches (146x127x51 cm) |

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667  
330.683.0075 • 1.866.VENTRAC  
Fax: 330.683.0000  
[www.ventrac.com](http://www.ventrac.com) • [info@ventrac.com](mailto:info@ventrac.com)