

Ventrac's Triplex **Reel Mower** features a 74-inch cutting width and is designed to be the ultimate trim and surround mower.

The MR740 uses reel heads manufactured **BARONESS** by Baroness® providing you with 100 years of experience and the highest quality turf maintenance equipment in the world.

Several design features on the MR740 make operating and servicing the reel mower simple. Features include variable speed hydraulics, standard back lapping valves, and offset capability to ensure superior, low-maintenance performance.

Three well balanced reel units feature the exceptional ability to follow ground contours at highly productive speeds, without rear roller hopping



Standard Features:

- Fully serviceable and easy to maintain
- Superior edge retention and life for the bedknife and reel
- Low pressure, low temperature Hydraulic Reel Drive for long-lasting service
- Identical reel heads are simple and easy to change.
- Transport locks keep reel heads in raised position for transportation and storage
- Bypass valves enable/disable each motor individually
- Simple & quick reel speed adjustment
- Fully adjustable grass discharge deflectors
- Ventrac Mount System

REQUIRED: Spool float kit (23.0111-7) required on 4000 series tractor to operate MR740.



Specifications

Mower - Reel Mower MR740

4000
series

MR740

Stock Code	39.55130
Deck Type	Front Mount, Triplex Reels
Deck Suspension	Front Roller (grooved) Rear Roller (smooth)
Width of Cut	74 inches (188 cm)
Cutting Height Range	.39 inch (10mm) to 2.36-inches (60mm)
Cutting Positions	Infinite
Cutting Height Adjustment	Multi-point
Discharge Type	Fully adjustable

Required

Kit, Spool float	23.0111-7
------------------	-----------

Dimensions

Length	48 inches (122cm)
Width	84 inches (214cm)
Height	22 inches (56 cm)
Weight	613 lbs (278 kg)
Shipping Dimensions (LWH)	55x48x45 inches (140x122x114 cm)

Reel Specifications

Reel Drive	Hydraulic
Reel Speed	Variable
Backlapping	Standard, with Individual Bypass Valves
Cutting Units	3
Reel Length	26-inches (66 cm)
Reel Diameter	7 inches (18 cm)
Reel Blades	7
Adjustment	Reel to Bedknife

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com